

S-1245 Resilient seat gate valve DN 40-500

02-23/1039003091/01.2007 **2**

Page 1 of 1

Application and features

- S-1245 equivalent to S-1240, with the following exceptions:
Rubber (NBR) in wedge

Clockwise closing.

Also to be delivered as counterclockwise closing (S-1246).

Illustration shows S-1245 DN 150. For further information regarding these products, see separate sheets:

DN 40-50: [\[S-1140/S-1240 DN 40-50\]](#)

DN 65: [\[S-1140/S-1240 DN 65\]](#)

DN 80-150: [\[S-1140/S-1240 DN 80-150\]](#)

DN 200-300: [\[S-1140/S-1240 DN 200-300\]](#)

DN 400/400-500: [\[S-1140/S-1240 DN 400/400-500\]](#)



References and dimensions

DN mm	Flange-drilling	Esco no.	Danfoss no.
40	PN 10	12450040	149L145200
50	PN 10	12450050	149L145300
65	PN 10	12450065	149L145400
80	PN 10	12450080	149L145500
100	PN 10	12450100	149L145700
125	PN 10	12450125	149L145800
150	PN 10	12450150	149L145900
200	PN 10	12450205	
200	PN 16	12450206	
250	PN 10	12450250	149L146200
250	PN 16	12450251	149L143000
300	PN 10	12450300	149L146400
300	PN 16	12450301	149L146500
400	PN 10	12450400	149L183900
400	PN 16	12450401	149L184000
500	PN 10	12450500	
500	PN 16	12450501	

Kongsberg Esco AS can accept no responsibility for possible errors in catalogues, brochures and other printed material. Kongsberg Esco AS reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequent changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Kongsberg Esco and the Kongsberg Esco logotype are trademarks of Kongsberg Esco AS. All rights reserved.